7720-EN-01 DTIC

## BRIEF REVIEW OF PROPOSALS FOR SECOND PROJECT ON APPLYING GEOSTATISTICS TO REMOTE IMAGERY OF FORT BELVOIR

First Interim Report (RSSUSA - 2/1)

Dr Margaret A. Oliver and Professor Richard Webster September 1995 to November 1995


United States Army

ENVIRONMENTAL RESEARCH OFFICE OF THE U.S. ARMY

London, England

CONTRACT NUMBER - N68171 - 95 - C - 9128

Contractor - Approved for Public Release; distribution unlimited



19960212 185

DTIC QUALITY INSPECTED 4

REPORT DOCUMENTATION PAGE	form Approved CM8 No. 0704-0188
Command transfer indirection and property for induction for the property of indirection of the property for	Intermed Instructions, or although evidence data source or idence this burger interests or any nature stored of the or information Constraint and Emports, 1815 (extremos pression 2004) 1818, Washington, OC (2701).
1. AGENCY USE ONLY (Leave diank) 2. REPORT DATE 13. REPORT TYPE AND 10.12.95 Interim - Se	o oa res covere ept 1995-Nov 1995
4. TITLE AND SUBTITLE	3. FUNCING NUMBERS
Brief review of proposals for second project on applying geostatistics to remote imagery of Fort Belvoir  5. AUTHOR(S)  Dr M A Oliver, Professor R Webster	N68171 95-C9218
	•
7. PERFORMING ORGANIZATION MAME(S) AND ADDRESS(ES)	3. PERFORMING ORGANIZATION REPORT NUMBER
University of Reading, Whiteknights,	
Reading, RG6 2AH, UK	RSS USA-2
9. SPONSORING, MONITORING AGENCY NAME(S) AND ADDRESS(ES)	O. SPONSORING, MONITORING AGENCY REPORT YUMBER
USARDSG-UK, Environmental Sciences Branch Edison House, 233 Old Marylebone Road, London, NW1 5TH, UK	A CONTRACTOR OF THE CONTRACTOR
1. SUPPLEMENTARY NOTES	· ·
We are waiting to receive the SPOT image for Fort Belvoir	15. 015 TAISUTIGH CODE
No limitation on distribution/availability	
D. ABSTRACT (Maximum 200 words)	
This is the first report on the second phase of the project to remote imagery. The main focus of the research will be to minimize the amount of data needed to be stored from removed in the removed by sampling the image optimally and retaining that is essential to restore the image at a particular spatial resultant been chosen for the second analysis. On receipt of the impreliminary analyses: compute summary statistics, variogram analysis and mapping of the wavebands. Using the variogram the kriging equations for a range of sampling intervals an optimilar will be determined to enable the image to be reconstructed at a	o use geostatistics to otely sensed images. ctral images, and this gonly that information solution. Fort Belvoir nage data we shall deanalyses, correlation models and solving mal sampling interval
SUBJECT TERMS	15. NUMBER OF PAGES
Fort Belvoir, optimal sampling, image reconstruction, redundancy, kriging, variogram.	16. PRICE CODE
SECURITY CLASSIFICATION IS. SECURITY CLASSIFICATION 19. SECURITY CLASSIFICATION OF THIS PAGE OF ABSTRACT	N 20. UMITATION OF ASSTRACT

- NSN 7540-01-180-5500

Standard Form 193 (Rév. 1-89) Printrome by anti-tia (19-16 196-102)

## ABSTRACT

This first report of the second phase of the project to apply geostatistics to remote imagery summarises the focus of the research. We shall base the preliminary analysis of the image on what we learned in the first phase. The SPOT image will cover Fort Belvoir which has a variety of types of land cover. Based on the resolution required we shall sample the image optimally and use the exhaustive variogram from the whole image to reconstruct the image from the sample values.

## SUMMARY OF PROPOSED SCHEME OF WORK

This is the first report on the second phase of the project to apply geostatistics to remote imagery. The first phase dealt with analysing the spatial structure in the information from three wavebands of a SPOT image for a part of Fort Benning. This was then related to the spatial structure in the ground cover, and it was used to design a sampling scheme for ground survey of the part studied. The second phase will focus on using geostatistics to minimize the amount of data from remotely sensed images that needs to be stored to enable the pattern of variation to be reconstruction at a prescribed precision or resolution.

There is much redundant information in most spectral images, and this can be removed by sampling the image optimally and retaining only the information that is essential to restore the image at a particular spatial resolution. The previous analysis showed that there were two distinct spatial scales of variation in the pixel information and that the shorter scale related to the variation in ground cover. To remove redundant information the image could be sampled optimally in relation to either or both of these spatial scales. This would then dictate the resolution of the reconstructed image. The choice would depend on what detail of information was likely to be required by future users. Ideally a reconstruction based on the shorter scale should be aimed for because this would provide most of the information likely to be required in the future.

Fort Belvoir in Fairfax County, Virginia, has been chosen for the second analysis. At the moment we are waiting for the SPOT image information for the site to arrive (it has been ordered). There are several advantages of working with this site. It is

readily accessible for ground surveys by the staff at TEC who are already based there. Full colour aerial photography of the ground cover is already available. This means that field observation can be minimized, and the photographs can also be used for testing classifications based on the pixel information.

Fort Belvoir covers 8656 acres, and there is a considerable variety in the land use. It includes field training zones, open space and environmentally sensitive areas with forest and a wildlife corridor, recreation areas such as a golf course, an airfield and research areas in which there are three main projects already. In addition there are built up areas that include the research offices and administrative blocks, housing, a hospital and roads. The largest areas include those covered by research (15.5 %), open space and environmentally sensitive areas (26 %), training areas (10.8 %), and built up areas (21 %).

On receipt of the image data we shall do a preliminary analysis in preparation for the main research. This will include computing summary statistics, variogram analyses, correlation analysis and mapping of the wavebands. This will enable us to determine what the spatial structures present in the variation are and whether there is any redundancy in the wavebands. If so we shall concentrate on those bands that are uncorrelated. If there are distinct scales of spatial variation then we shall want project members at TEC to identify the scale or scales that are of interest to them. This will provide the basis for designing the sampling scheme to compare the ground cover information with that in the image. If the ground cover scales reflect those in the image then we can design a sampling scheme to sample the image optimally using the kriging equations that will contain all of the essential information about the variation in ground cover that needs to be saved. By selecting a range of sampling intensities and solving the kriging equations for each a graph of prediction variance against sampling interval can be drawn, and then for any given tolerance the sampling interval can be read from the graph. Based on an optimal sampling interval we should then enable us to reconstruct the image at a resolution that reflects the ground cover or any other resolution that is deemed valuable for restoring information likely to be required.